





CANVIEW 3

SPECIFICHE TECNICHE:

Tensione di alimentazione:	12V
Temperatura di funzionamento:	- 30 °C ÷ + 75 °C
Temperatura di stoccaggio:	- 35 °C ÷ + 85 °C
Grado di protezione frontale:	IP66
Grado di protezione posteriore:	IPO0
Prove di qualificazione:	standard Unideck (UKCPST001)
Dimensioni:	98 x 58 mm
Connettore:	Molex 6 vie serie MINI FIT
Controparte:	Molex codice 39 - 01 - 2060 Pin codice 39 - 00 - 0038
Comunicazione:	CAN BUS
Display LCD:	176 x 80 a matrice di punti
Retroilluminazione:	LED
Buzzer:	integrato
Fissaggio:	molle a scatto
Assemblaggio su plancia:	anteriore
Note:	predisposizione touch screen
Applicazioni:	strumento compatibile con Winscope e Winloader

TECHNICAL SPECIFICATIONS:

Power supply voltage:	12V
Operating temperature:	- 30 °C ÷ + 75 °C
Storage temperature:	- 35 °C ÷ + 85 °C
Front sealing:	IP66
Rear sealing:	IPO0
Qualification test:	Unideck standard (UKCPST001)
Size:	98 x 58 mm
Connector:	Molex 6 pins MINI FIT series
Mating connector:	Molex code 39 - 01 - 2060 Pin code 39 - 00 - 0038
Serial communication:	CAN BUS
LCD Display:	dot matrix 176 x 80
Backlight:	LED
Buzzer:	integrated
Fixing:	snap springs
Dashboard assembling:	front
Notes:	touch screen available
Applications:	compliant with Winscope and Winloader

